

Flat-type Ethernet Switches

| Model | Unmanaged PoE+ | | | Unmanaged | |
|---------------|---|---|---|---|---|
| | WGS-818HP | WGS-814HP | WGS-804HP | WGS-810 | WGS-803 |
| Product Image |  |  |  |  |  |
| Hardware | 10/100/1000BASE-T | 8 | 8 | - | 8 |
| | 1000BASE-X SFP | - | - | - | - |
| | Switch Fabric | 16Gbps | 16Gbps | - | 16Gbps |
| | DIP Switch | Standard/VLAN/Extend | | | Standard/VLAN/Extend |
| Power | Inputs | 48~56V DC | 48~56V DC | Dual 48~56V DC | 12V DC |
| | Connector | DC socket | DC socket | 3-pin terminal block, DC socket | DC socket |
| | Consumption | 137 watts | 70 watts | 140 watts | 4 watts |
| Mechanical | Dimensions (W x D x H) | 148 x 25 x 134 mm | 148 x 25 x 134 mm | 148 x 25 x 134 mm | 148 x 25 x 134 mm |
| | Enclosure | IP30 metal | IP30 metal | IP30 metal | IP30 metal |
| | Mounting | DIN-rail, wall-mountable and magnetic wall mount | | | |
| Environment | Operating Temperature | -20~60 degrees C | -20~60 degrees C | -40~75 degrees C | -20~60 degrees C |
| Regulatory | Emissions | FCC Class A, CE | FCC Class A, CE | FCC Class A, CE | FCC Class A, CE |
| | Stability | FCC Class A, CE Class A | | FCC Class A, CE Class A | FCC Class A, CE Class A |
| PoE | PoE Standard | 802.3at PoE+ | 802.3at PoE+ | 802.3at PoE+ | - |
| | PoE Port | 8 | 4 | 4 | - |
| | PoE Budget | 120W | 60W | 120W | - |

Industrial Flat-type Gigabit Router

Wall-mount Design, Perfect for Public Facilities

PLANET WGR-500 Series, an all-in-one router solution suitable for industrial applications, features 4-port 10/100/1000BASE-T Gigabit Ethernet and 1-port 100/1000BASE-T Gigabit Ethernet. It offers Layer 3 dynamic IP (DHCP Client), static IP, PPPoE, L2TP, PPTP, intelligent Layer 2 and Layer 4 management functions, and user-friendly interface.

Equipped with 4-port 802.3at PoE+ and in-line power interfaces, the WGR-500-4PV and WGR-500-4P centrally manage power supply to PoE IP cameras and PoE sensors at factories. The WGR-500 Series provides firewall to protect IoT devices against networking attack such as denial-of-service (DoS) and emerging malicious traffic before attacks occur. With firewall protection, it prevents IoT network from threats and keeps networking secure. The WGR-500 series is an ideal solution to meet the demand for the following network applications:

- Building/Home automation network
- Internet of things (IoT)
- IP surveillance
- Wireless LAN



| Model | Touch LCD | Managed PoE+ | |
|---------------|---|---|---|
| | WGR-500-4PV | WGR-500-4P | WGR-500 |
| Product Image |  |  |  |
| Hardware | LCD | 2.4" Color TFT Touch Screen | - |
| | 10/100/1000BASE-T | 5 (4 LAN, 1 WAN) | 5 (4 LAN, 1 WAN) |
| Power | Inputs | Dual 48~56V DC | Dual 48~56V DC |
| | Connector | 3-pin terminal block, DC socket | 3-pin terminal block, DC socket |
| Mechanical | Dimensions (W x D x H) | 180 x 25 x 140 mm | 180 x 25 x 140 mm |
| | Enclosure | IP30 metal | IP30 metal |
| | Mounting | DIN-rail, wall-mountable and magnetic wall mount | |
| Environment | Operating Temperature | -10~60 degrees C | -10~60 degrees C |
| Regulatory | Emissions | FCC Class A, CE Class A | FCC Class A, CE Class A |
| | Stability | IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration) | |
| PoE | PoE Standard | 802.3at PoE+ | 802.3at PoE+ |
| | PoE Port | 4 | 4 |
| | PoE Budget | 120 watts | 120 watts |
| | Power Pin Assignment | 1/2(+), 3/6(-) | 1/2(+), 3/6(-) |
| Protocol | VLAN | IEEE 802.1Q VLAN | IEEE 802.1Q VLAN |
| Management | Interface | Web | Web |
| | SNMP | v1, v2c | v1, v2c |
| | System Log | System log and remote Syslog | System log and remote Syslog |



Ethernet Switch

Gigabit Router

All-Inclusive Industrial Flat-type Ethernet Perfect IP Network Deployment for Buildings and Factories



Flat-type Ethernet Switches



Security Building Automation Switches

Suitable for buildings where security is strictly to be enforced, PLANET Industrial Wall-mount Managed Switches offer a comprehensive Layer 2 to Layer 4 Access Control List (ACL). The switches can restrict network access by denying packets based on source and destination IP address, TCP/UDP ports or defined typical network applications. The WGS-5225 Series incorporates advanced ITU-T G.8032 ERPS (Ethernet Ring Protection Switching) technology into customer's industrial automation network to enhance system reliability and uptime. With PLANET Industrial Wall-mount Managed Switches, a tightly-controlled network can be easily had in no time.

FTTX/MAN Application

PLANET Industrial Wall-mount Managed Switches adopt the double tagged VLAN (Q-in-Q) technology to provide low cost and easy operation for service providers carrying traffic for multiple customers across their networks. With two dual-speed SFP slots built in, the deployment distance of PLANET Industrial Wall-mount Managed Switches can be extended up to 120 kilometers (single-mode fiber), which provides a high-performance edge service for FTTx solutions.



To build a network solution of FTTH (Fiber to the Home) or FTTC (Fiber to the Curb) for ISPs, and FTTB (Fiber to the Building) for enterprises, the various distances of SFP and BiDi (WDM) transceivers are optional for customers. For security and various applications, the 8 Gigabit ports of PLANET Industrial Wall-mount Managed Switches can be configured with VLAN settings and connected to different units, offices, floors, houses and departments.

Unique Flat-type Design with Touch LCD Screen or PoE Functions for Efficient Management



To facilitate the network deployment in any space-limited locations like wall enclosure or electric box found in buildings or outdoors, PLANET has the industrial Ethernet switches and wireless AP designed in a compact flat type. The products can be installed by fixed wall mounting, magnetic wall mounting or DIN rail, thereby making its usability more flexible. With the intuitive LCD Touch Screen or PoE Functions including PD alive check, scheduled power recycling, PoE schedule and PoE usage monitoring, PLANET's flat-type switches greatly promote efficient and timely network management, perfectly suitable for surveillance, wireless and VoIP networks.

| | | Touch LCD | | Managed | |
|---------------|------------------------|---|------------------------------|---------------------------------|---------------------|
| Model | | WGS-5225-8T2SV | WGS-5225-8P2SV | WGS-4215-8T | WGS-4215-8T2S |
| Product Image | | | | | |
| Hardware | LCD | 2.4" Color TFT Touch Screen | | | |
| | 10/100/1000BASE-T | 8 | 8 | 8 | 8 |
| | 1000 mini-GBIC | 2, Compatible with 2500X SFP | 2, Compatible with 2500X SFP | - | 2 |
| | 100BASE-FX | Compatible | Compatible | - | Compatible |
| Power | Switch Fabric | 26Gbps | 26Gbps | 16Gbps | 20Gbps |
| | Inputs | 12~48V DC or 24V AC | Dual 48~56V DC | 12~48V DC or 24V AC | 12~48V DC or 24V AC |
| | Connector | 3-pin terminal block, DC socket | | 3-pin terminal block, DC socket | |
| | Consumption | 12 watts | 251 watts | 10 watts | 7.9 watts |
| Mechanical | Dimensions (W x D x H) | 180 x 25 x 140 mm | 180 x 25 x 140 mm | 148 x 25 x 134 mm | 178 x 25 x 134 mm |
| | Enclosure | IP30 metal | IP30 metal | IP30 metal | IP30 metal |
| Environment | Mounting | DIN-rail, wall-mountable and magnetic wall mount | | | |
| | Operating Temperature | -20~70 degrees C | -20~70 degrees C | -40~75 degrees C | -40~75 degrees C |
| Regulatory | Operating Humidity | 5% to 95%RH (non-condensing) | | 5% to 95%RH (non-condensing) | |
| | Emissions | FCC Class A, CE Class A | | | |
| | Stability | IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration) | | | |
| PoE | PoE Standard | - | 802.3at PoE+ | - | - |
| | PoE Port | - | 8 | - | - |
| | PoE Budget | - | 240 watts | - | - |
| | PSE Type | - | End span | - | - |
| Protocol | Power Pin Assignment | - | 1/2(+), 3/6(-) | - | - |
| | VLAN | IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP | | | |
| | IGMP Snooping | v2/v3/query | v2/v3/query | v2/v3/query | v2/v3/query |
| | Spanning Tree | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s |
| | Data Redundancy | ERPS Ring, RSTP/MSTP | | ERPS Ring, RSTP/MSTP | |
| | QoS | Port-based/802.1P/IP DSCP Policy-based/Voice VLAN | | | |
| | Security | 802.1x, Static MAC, MAC filter, Port Security and IP Security | | | |
| Management | Traffic Control | In/out rate limit, storm control | | | |
| | Interface | Web, telnet, SSH and SSL | | | |
| | SNMP | v1, v2c, v3 and trap | | | |
| | System Log | System log and remote Syslog | | | |

| | | Managed PoE+ | | | | | |
|---------------|------------------------|---|--|---------------------------------|-------------------|----------------------------------|--|
| Model | | WGS-5225-8UP2SV | WGS-5225-8P2S | WGS-4215-16P2S | WGS-4215-8P2S | WGS-4215-8HP2S | WGS-804HPT |
| Product Image | | | | | | | |
| Hardware | LCD | - | - | - | - | - | - |
| | 10/100/1000BASE-T | 8 | 8 | 16 | 8 | 8 | 8 |
| | 1000 mini-GBIC | 2, Compatible with 2500X SFP | 2, Compatible with 2500X SFP | 2 | 2 | 2 | - |
| | 100BASE-FX | Compatible | Compatible | Compatible | Compatible | Compatible | - |
| Power | Switch Fabric | 26Gbps | 26Gbps | 32Gbps | 20Gbps | 20Gbps | 16Gbps |
| | Inputs | Dual 48~54V DC | Dual 48~56V DC | Dual 48~56V DC | Dual 48~56V DC | Dual 48~54V DC | Dual 48~56V DC |
| | Connector | 4-pin terminal block | 3-pin terminal block, DC socket | 3-pin terminal block, DC socket | | | |
| | Consumption | 752 watts | 250 watts | 250 watts | 210 watts | 382 watts | 152 watts |
| Mechanical | Dimensions (W x D x H) | 245 x 36 x 140 mm | 180 x 25 x 140 mm | 245 x 25 x 134 mm | 178 x 25 x 134 mm | 245 x 36 x 140 mm | 148 x 25 x 134 mm |
| | Enclosure | IP30 Aluminum | IP30 metal | IP30 metal | IP30 metal | IP30 metal | IP30 metal |
| Environment | Mounting | Wall-mountable | DIN-rail, wall-mountable and magnetic wall mount | | | Wall-mountable | DIN-rail, wall-mountable and magnetic wall mount |
| | Operating Temperature | -20~70 degrees C | -40~75 degrees C | -10~60 degrees C | -40~75 degrees C | -40~75 degrees C | -40~75 degrees C |
| Regulatory | Operating Humidity | 5% to 95%RH (non-condensing) | | | | 5% to 95%RH (non-condensing) | |
| | Emissions | FCC Class A, CE Class A | | | | FCC Class A, CE Class A | |
| | Stability | IEC60068-2-32 (Free Fall), IEC60068-2-27 (Shock), EC60068-2-6 (Vibration) | | | | | |
| PoE | PoE Standard | 802.3bt PoE++ | 802.3at PoE+ | 802.3at PoE+ | 802.3at PoE+ | 802.3bt PoE++ | 802.3at PoE+ |
| | PoE Port | 8 | 8 | 16 | 8 | 8 | 4 |
| | PoE Budget | 720 watts | 240 watts | 240 watts | 240 watts | 360 watts | 144 watts |
| | PSE Type | End span + Mid span | End span | End span | End span | End span + Mid span | End span |
| Protocol | Power Pin Assignment | 1/2(-), 3/6(+) 4/5(+), 7/8(-) | 1/2(+), 3/6(-) | 1/2(+), 3/6(-) | 1/2(+), 3/6(-) | 1/2(-), 3/6(+) 4/5(+), 7/8(-) | 1/2(+), 3/6(-) |
| | VLAN | IEEE 802.1Q VLAN/Q-in-Q/Private VLAN/Protocol-based VLAN/Voice VLAN/GVRP | | | | | |
| | IGMP Snooping | v2/v3/query | v2/v3/query | v2/v3/query | v2/v3/query | v2/v3/query | v2/v3/query |
| | Spanning Tree | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s | 802.1w/802.1s |
| | Data Redundancy | ERPS Ring < 10ms | | ERPS Ring, RSTP/MSTP | | ERPS Ring, RSTP/MSTP | |
| | QoS | Port-based/802.1P/IP DSCP Policy-based/Voice VLAN | | | | | |
| | Security | 802.1x, Static MAC, MAC filter, Port Security and IP Security | | | | | |
| Management | Traffic Control | In/out rate limit, storm control | | | | | |
| | Interface | Web, telnet, SSH and SSL | | | | | |
| | SNMP | v1, v2c, v3 and trap | | | | | |
| | System Log | System log and remote Syslog | | | | | |