

COPPER TERMINALS



terminals . connectors . wiring accessories
MARROW LIN
DEVELOPMENT CO., LTD.

RING TERMINAL - JIS STANDARD

MATERIAL: COPPER SURFACE: TIN PLATED

unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Flared W/ Brazed	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.2	VR1-3.2	VR1-3.2D	VR1-3.2NB	IVR1-3.2	IMR1-3.2	INR1-3.2
		3.7	VR1-3M	VR1-3MD	VR1-3MNB	IVR1-3M	IMR1-3M	INR1-3M
		3.7	VR1-3	VR1-3D	VR1-3NB	IVR1-3	IMR1-3	INR1-3
		4.3	VR1-4M	VR1-4MD	VR1-4MNB	IVR1-4M	IMR1-4M	INR1-4M
		4.3	VR1-4	VR1-4D	VR1-4NB	IVR1-4	IMR1-4	INR1-4
		5.3	VR1-5	VR1-5D	VR1-5NB	IVR1-5	IMR1-5	INR1-5
		6.4	VR1-6	VR1-6D	VR1-6NB	IVR1-6	IMR1-6	INR1-6
		8.4	VR1-8	VR1-8D	VR1-8NB	IVR1-8	IMR1-8	INR1-8
		10.5	VR1-10	VR1-10D	VR1-10NB	IVR1-10	IMR1-10	INR1-10
	1.5-2.5mm ² 16-14 AWG	3.2	VR2-3.2	VR2-3.2D	VR2-3.2NB	IVR2-3.2	IMR2-3.2	INR2-3.2
		3.7	VR2-3	VR2-3D	VR2-3NB	IVR2-3	IMR2-3	INR2-3
		3.7	VR2-3M	VR2-3MD	VR2-3MNB	IVR2-3M	IMR2-3M	INR2-3M
		4.3	VR2-4M	VR2-4MD	VR2-4MNB	IVR2-4M	IMR2-4M	INR2-4M
		4.3	VR2-4	VR2-4D	VR2-4NB	IVR2-4	IMR2-4	INR2-4
		5.3	VR2-5	VR2-5D	VR2-5NB	IVR2-5	IMR2-5	INR2-5
		5.3	VR2-5L	VR2-5LD	VR2-5LNB	IVR2-5L	IMR2-5L	INR2-5L
		6.4	VR2-6	VR2-6D	VR2-6NB	IVR2-6	IMR2-6	INR2-6
		8.4	VR2-8	VR2-8D	VR2-8NB	IVR2-8	IMR2-8	INR2-8
	4.0-6.0mm ² 12-10 AWG	10.5	VR2-10	VR2-10D	VR2-10NB	IVR2-10	IMR2-10	INR2-10
		3.7	VR5-3	VR5-3D	VR5-3NB	IVR5-3	IMR5-3	INR5-3
		4.3	VR5-4	VR5-4D	VR5-4NB	IVR5-4	IMR5-4	INR5-4
		5.3	VR5-5	VR5-5D	VR5-5NB	IVR5-5	IMR5-5	INR5-5
		6.4	VR5-6	VR5-6D	VR5-6NB	IVR5-6	IMR5-6	INR5-6
		8.4	VR5-8	VR5-8D	VR5-8NB	IVR5-8	IMR5-8	INR5-8
		10.5	VR5-10	VR5-10D	VR5-10NB	IVR5-10	IMR5-10	INR5-10
		13.0	VR5-12	VR5-12D	VR5-12NB	IVR5-12	IMR5-12	INR5-12

RING TERMINAL - DIN STANDARD

MATERIAL: COPPER SURFACE: TIN PLATED

unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Flared W/ Brazed	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	2.8	VA2.5-1	VA2.5-1D	VA2.5-1NB	IVA2.5-1	IMA2.5-1	INA2.5-1
		3.2	VA3-1	VA3-1D	VA3-1NB	IVA3-1	IMA3-1	INA3-1
		3.7	VA3.5-1	VA3.5-1D	VA3.5-1NB	IVA3.5-1	IMA3.5-1	INA3.5-1
		4.4	VA4-1	VA4-1D	VA4-1NB	IVA4-1	IMA4-1	INA4-1
		5.3	VA5-1	VA5-1D	VA5-1NB	IVA5-1	IMA5-1	INA5-1
		6.5	VA6-1	VA6-1D	VA6-1NB	IVA6-1	IMA6-1	INA6-1
		8.4	VA8-1	VA8-1D	VA8-1NB	IVA8-1	IMA8-1	INA8-1
		10.5	VA10-1	VA10-1D	VA10-1NB	IVA10-1	IMA10-1	INA10-1
		13.0	VA12-1	VA12-1D	VA12-1NB	IVA12-1	IMA12-1	INA12-1
	1.5-2.5mm ² 16-14 AWG	3.2	VA3-2.5	VA3-2.5D	VA3-2.5NB	IVA3-2.5	IMA3-2.5	INA3-2.5
		3.7	VA3.5-2.5	VA3.5-2.5D	VA3.5-2.5NB	IVA3.5-2.5	IMA3.5-2.5	INA3.5-2.5
		4.4	VA4-2.5	VA4-2.5D	VA4-2.5NB	IVA4-2.5	IMA4-2.5	INA4-2.5
		5.3	VA5-2.5	VA5-2.5D	VA5-2.5NB	IVA5-2.5	IMA5-2.5	INA5-2.5
		6.5	VA6-2.5	VA6-2.5D	VA6-2.5NB	IVA6-2.5	IMA6-2.5	INA6-2.5
		8.4	VA8-2.5	VA8-2.5D	VA8-2.5NB	IVA8-2.5	IMA8-2.5	INA8-2.5
		10.5	VA10-2.5	VA10-2.5D	VA10-2.5NB	IVA10-2.5	IMA10-2.5	INA10-2.5
		13.0	VA12-2.5	VA12-2.5D	VA12-2.5NB	IVA12-2.5	IMA12-2.5	INA12-2.5
	4.0-6.0mm ² 12-10 AWG	4.4	VA4-6	VA4-6D	VA4-6NB	IVA4-6	IMA4-6	INA4-6
		5.3	VA5-6	VA5-6D	VA5-6NB	IVA5-6	IMA5-6	INA5-6
		6.5	VA6-6	VA6-6D	VA6-6NB	IVA6-6	IMA6-6	INA6-6
		8.4	VA8-6	VA8-6D	VA8-6NB	IVA8-6	IMA8-6	INA8-6
		10.5	VA10-6	VA10-6D	VA10-6NB	IVA10-6	IMA10-6	INA10-6
		13.0	VA12-6	VA12-6D	VA12-6NB	IVA12-6	IMA12-6	INA12-6

*Please send in query for an unlisted item or special request



SPADE TERMINAL - JIS STANDARD
MATERIAL: COPPER SURFACE: TIN PLATED

unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Flared W/ Brazed	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.2	VY1-3.2	VY1-3.2D	VY1-3.2NB	IVY1-3.2	IMY1-3.2	INY1-3.2
		3.7	VY1-3S	VY1-3SD	VY1-3SNB	IVY1-3S	IMY1-3S	INY1-3S
		3.7	VY1-3	VY1-3D	VY1-3NB	IVY1-3	IMY1-3	INY1-3
		4.3	VY1-4S	VY1-4SD	VY1-4SNB	IVY1-4S	IMY1-4S	INY1-4S
		4.3	VY1-4	VY1-4D	VY1-4NB	IVY1-4	IMY1-4	INY1-4
		4.3	VY1-4L	VY1-4LD	VY1-4LNB	IVY1-4L	IMY1-4L	INY1-4L
		5.3	VY1-5	VY1-5D	VY1-5NB	IVY1-5	IMY1-5	INY1-5
	6.4	VY1-6	VY1-6D	VY1-6NB	IVY1-6	IMY1-6	INY1-6	
	1.5-2.5mm ² 16-14 AWG	3.2	VY2-3.2	VY2-3.2D	VY2-3.2NB	IVY2-3.2	IMY2-3.2	INY2-3.2
		3.7	VY2-3S	VY2-3SD	VY2-3SNB	IVY2-3S	IMY2-3S	INY2-3S
		3.7	VY2-3	VY2-3D	VY2-3NB	IVY2-3	IMY2-3	INY2-3
		4.3	VY2-4S	VY2-4SD	VY2-4SNB	IVY2-4S	IMY2-4S	INY2-4S
		4.3	VY2-4	VY2-4D	VY2-4NB	IVY2-4	IMY2-4	INY2-4
		5.3	VY2-5	VY2-5D	VY2-5NB	IVY2-5	IMY2-5	INY2-5
		6.4	VY2-6	VY2-6D	VY2-6NB	IVY2-6	IMY2-6	INY2-6
	4.0-6.0mm ² 12-10 AWG	3.7	VY5-3	VY5-3D	VY5-3NB	IVY5-3	IMY5-3	INY5-3
		3.7	VY5-3M	VY5-3MD	VY5-3MNB	IVY5-3M	IMY5-3M	INY5-3M
		4.3	VY5-4S	VY5-4SD	VY5-4SNB	IVY5-4S	IMY5-4S	INY5-4S
		4.4	VY5-4	VY5-4D	VY5-4NB	IVY5-4	IMY5-4	INY5-4
		4.3	VY5-4M	VY5-4MD	VY5-4MNB	IVY5-4M	IMY5-4M	INY5-4M
		5.4	VY5-5	VY5-5D	VY5-5NB	IVY5-5	IMY5-5	INY5-5
		6.4	VY5-6	VY5-6D	VY5-6NB	IVY5-6	IMY5-6	INY5-6

SPADE TERMINAL - DIN STANDARD
MATERIAL: COPPER SURFACE: TIN PLATED


unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Flared W/ Brazed	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.2	VC3-1	VC3-1D	VC3-1NB	IVC3-1	IMC3-1	INC3-1
		3.7	VC3.5-1	VC3.5-1D	VC3.5-1NB	IVC3.5-1	IMC3.5-1	INC3.5-1
		4.3	VC4-1	VC4-1D	VC4-1NB	IVC4-1	IMC4-1	INC4-1
		5.3	VC5-1	VC5-1D	VYC5-1NB	IVC5-1	IMC5-1	INC5-1
		6.5	VC6-1	VC6-1D	VC6-1NB	IVC6-1	IMC6-1	INC6-1
	1.5-2.5mm ² 16-14 AWG	3.2	VC3-2.5	VC3-2.5D	VC3-2.5NB	IVC3-2.5	IMC3-2.5	INC3-2.5
		3.7	VC3.5-2.5	VC3.5-2.5D	VC3.5-2.5NB	IVC3.5-2.5	IMC3.5-2.5	INC3.5-2.5
		4.3	VC4-2.5	VC4-2.5D	VC4-2.5NB	IVC4-2.5	IMC4-2.5	INC4-2.5
		5.3	VC5-2.5	VC5-2.5D	VC5-2.5NB	IVC5-2.5	IMC5-2.5	INC5-2.5
		6.5	VC6-2.5	VC6-2.5D	VC6-2.5NB	IVC6-2.5	IMC6-2.5	INC6-2.5
	4.0-6.0mm ² 12-10 AWG	4.6	VC4-6	VC4-6D	VC4-6NB	IVC4-6	IMC4-6	INC4-6
		5.3	VC5-6	VC5-6D	VC5-6NB	IVC5-6	IMC5-6	INC5-6
		6.5	VC6-6	VC6-6D	VC6-6NB	IVC6-6	IMC6-6	INC6-6
		8.4	VC8-6	VC8-6D	VC8-6NB	IVC8-6	IMC8-6	INC8-6
		10.5	VC10-6	VC10-6D	VC10-6NB	IVC10-6	IMC10-6	INC10-6

FLANGED SPADE TERMINAL

MATERIAL: COPPER SURFACE: TIN PLATED


unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Flared W/ Braze	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.8	VFS1-3.5	N/A	N/A	IVFS1-3.5	IMFS1-3.5	INFS1-3.5
	1.5-2.5mm ² 16-14 AWG	3.8 4.4	VFS2-3.5 VFS2-4	N/A N/A	N/A N/A	IVFS2-3.5 IVFS2-4	IMFS2-3.5 IMFS2-4	INFS2-3.5 INFS2-4

LOCKING SPADE TERMINAL

MATERIAL: COPPER SURFACE: TIN PLATED

unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Uninsulated W/ Braze	Vinyl Flared W/ Braze	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.8	VLS1-3.5	LS1-3.5NB	VLS1-3.5NB	IVLS1-3.5	IMLS1-3.5	INLS1-3.5
	1.5-2.5mm ² 16-14 AWG	3.8	VLS2-3.5	LS2-3.5NB	VLS2-3.5NB	IVLS2-3.5	IMLS2-3.5	INLS2-3.5
	4.0-6.0mm ² 12-10 AWG	6.5	VLS5-6	LS5-6NB	VLS5-6NB	IVLS5-6	IMLS5-6	INLS5-6

PIN TERMINAL

MATERIAL: COPPER SURFACE: TIN PLATED



unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Uninsulated	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	12	VPT1	VPT1D	PT1	IVPT1	IMPT1	INPT1
		7	VPT1-7	VPT1-7D	PT1-7	IVPT1-7	IMPT1-7	INPT1-7
		9	VPT1-9	VPT1-9D	PT1-9	IVPT1-9	IMPT1-9	INPT1-9
		10	VPT1-10	VPT1-10D	PT1-10	IVPT1-10	IMPT1-10	INPT1-10
	1.5-2.5mm ² 16-14 AWG	12	VPT2	VPT2	PT2	IVPT2	IMPT2	INPT2
		9	VPT2-9	VPT2-9D	PT2-9	IVPT2-9	IMPT2-9	INPT2-9
		10	VPT2-10	VPT2-10D	PT2-10	IVPT2-10	IMPT2-10	INPT2-10
	4.0-6.0mm ² 12-10 AWG	17	VPT2-17	VPT2-17D	PT2-17	IVPT2-17	IMPT2-17	INPT2-17
		14	VPT5	VPT5D	PT5	IVPT5	IMPT5	INPT5
		9	VPT5-6	VPT5-6D	PT5-6	IVPT5-6	IMPT5-6	INPT5-6

BLADE TERMINAL

MATERIAL: COPPER SURFACE: TIN PLATED


unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Uninsulated	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	9.0	VB1-9	VB1-9D	BT1-9	IVBT1-9	IMBT1-9	INBT1-9
		10.5	VB1-10	VB1-10D	BT1-10	IVBT1-10	IMBT1-10	INBT1-10
		13.0	VB1-13	VB1-13D	BT1-13	IVBT1-13	IMBT1-13	INBT1-13
		14.5	VB1-14	VB1-14D	BT1-14	IVBT1-14	IMBT1-14	INBT1-14
		18.5	VB1-18	VB1-18D	BT1-18	IVBT1-18	IMBT1-18	INBT1-18
	1.5-2.5mm ² 16-14 AWG	9.0	VB2-9	VB2-9D	BT2-9	IVBT2-9	IMBT2-9	INBT2-9
		10.5	VB2-10	VB2-10D	BT2-10	IVBT2-10	IMBT2-10	INBT2-10
		13.0	VB2-13	VB2-13D	BT2-13	IVBT2-13	IMBT2-13	INBT2-13
		16.0	VB2-16	VB2-16D	BT2-16	IVBT2-16	IMBT2-16	INBT2-16
		18.5	VB2-18	VB2-18D	BT2-18	IVBT2-18	IMBT2-18	INBT2-18
	4.0-6.0mm ² 12-10 AWG	10.0	VB5-10	VB5-10D	BT5-10	IVBT5-10	IMBT5-10	INBT5-10
		18.2	VB5-18	VB5-18D	BT5-18	IVBT5-18	IMBT5-18	INBT5-18

HOOKEED BLADE TERMINAL

MATERIAL: COPPER SURFACE: TIN PLATED



unit: mm

	Wire Range	Stud Length	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Uninsulated	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.0	VHB1-17	VHB1-17D	HB1-17	IVHB1-17	N/A	N/A
		4.6	VHB1-17-4.6	VHB1-17-4.6D	HB1-17-4.6	N/A	N/A	N/A
	1.5-2.5mm ² 16-14 AWG	3.0	VHB2-17	VHB2-17	HB2-17	IVHB2-17	N/A	N/A
		4.6	VHB2-17-4.6	VHB2-17-4.6D	HB2-17-4.6	N/A	N/A	N/A

INSULATED FEMALE PUSH-ON DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED




unit: mm

	Wire Range	To Fit Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	2.8 x 0.5	VD1-2.8F5	VD1-2.8F5C	IVD1-2.8F5	IMD1-2.8F5	IND1-2.8F5
		2.8 x 0.8	VD1-2.8F8	VD1-2.8F8C	IVD1-2.8F8	IMD1-2.8F8	IND1-2.8F8
		4.8 x 0.5	VD1-4.8F5	VD1-4.8F5C	IVD1-4.8F5	IMD1-4.8F5	IND1-4.8F5
		4.8 x 0.8	VD1-4.8F8	VD1-4.8F8C	IVD1-4.8F8	IMD1-4.8F8	IND1-4.8F8
		6.3 x 0.8	VD1-6.3F	VD1-6.3FC	IVD1-6.3F	IMD1-6.3F	IND1-6.3F
		7.9 x 0.8	VD1-8F	VD1-8FC	N/A	N/A	N/A
	1.5-2.5mm ² 16-14 AWG	2.8 x 0.5	VD2-2.8F5	VD2-2.8F5C	IVD2-2.8F5	IMD2-2.8F5	IND2-2.8F5
		2.8 x 0.8	VD2-2.8F8	VD2-2.8F8C	IVD2-2.8F8	IMD2-2.8F8	IND2-2.8F8
		4.8 x 0.5	VD2-4.8F5	VD2-4.8F5C	IVD2-4.8F5	IMD2-4.8F5	IND2-4.8F5
		4.8 x 0.8	VD2-4.8F8	VD2-4.8F8C	IVD2-4.8F8	IMD2-4.8F8	IND2-4.8F8
		6.3 x 0.8	VD2-6.3F	VD2-6.3FC	IVD2-6.3F	IMD2-6.3F	IND2-6.3F
		7.9 x 0.8	VD2-8F	VD2-8FC	IVD2-8F	IMD2-8F	IND2-8F
		9.5 x 1.2	VD2-9.5F	VD2-9.5C	IVD2-9.5F	IMD2-9.5F	IND2-9.5F
	4.0-6.0mm ² 12-10 AWG	6.3 x 0.8	VD5-6.3F	VD5-6.3FC	IVD5-6.3F	IMD5-6.3F	IND5-6.3F
		9.5 x 1.2	VD5-9.5F	VD5-9.5FC	IVD5-9.5F	IMD5-9.5F	IND5-9.5F

INSULATED MALE PUSH-ON DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED




unit: mm

	Wire Range	To Fit Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	2.8 x 0.5	VD1-2.8M5	VD1-2.8M5C	IVD1-2.8M5	IMD1-2.8M5	IND1-2.8M5
		2.8 x 0.8	VD1-2.8M8	VD1-2.8M8D	IVD1-2.8M8	IMD1-2.8M8	IND1-2.8M8
		4.8 x 0.5	VD1-4.8M5	VD1-4.8M5C	IVD1-4.8M5	IMD1-4.8M5	IND1-4.8M5
		4.8 x 0.8	VD1-4.8M8	VD1-4.8M8D	IVD1-4.8M8	IMD1-4.8M8	IND1-4.8M8
		6.3 x 0.8	VD1-6.3M	VD1-6.3MC	IVD1-6.3M	IMD1-6.3M	IND1-6.3M
	1.5-2.5mm ² 16-14 AWG	2.8 x 0.5	VD2-2.8M5	VD2-2.8M5C	IVD2-2.8M5	IMD2-2.8M5	IND2-2.8M5
		2.8 x 0.8	VD2-2.8M8	VD2-2.8M8D	IVD2-2.8M8	IMD2-2.8M8	IND2-2.8M8
		4.8 x 0.5	VD2-4.8M5	VD2-4.8M5C	IVD2-4.8M5	IMD2-4.8M5	IND2-4.8M5
		4.8 x 0.8	VD2-4.8M8	VD2-4.8M8D	IVD2-4.8M8	IMD2-4.8M8	IND2-4.8M8
		6.3 x 0.8	VD2-6.3M	VD2-6.3MC	IVD2-6.3M	IMD2-6.3M	IND2-6.3M
	4.0-6.0mm ² 12-10 AWG	6.3 x 0.8	VD5-6.3M	VD5-6.3MC	IVD5-6.3M	IMD5-6.3M	IND5-6.3M

PIGGY BACK DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED



unit: mm

	Wire Range	To Fit Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
  	0.5-1.5mm ² 22-16 AWG	6.3 x 0.8	VD1-6.3FM	VD1-6.3FMC	IVD1-6.3FM	IMD1-6.3FM	IND1-6.3FM
	1.5-2.5mm ² 16-14 AWG	6.3 x 0.8	VD2-6.3FM	VD2-6.3FMC	IVD2-6.3FM	IMD2-6.3FM	IND2-6.3FM
	4.0-6.0mm ² 12-10 AWG	6.3 x 0.8	VD5-6.3FM	VD5-6.3FMC	IVD5-6.3FM	IMD5-6.3FM	IND5-6.3FM

FULLY INSULATED FEMALE PUSH-ON DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED




unit: mm

	Wire Range	To Fit Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	2.8 x 0.5	N/A	LVD1-2.8F5C	N/A	N/A	N/A
		2.8 x 0.8	N/A	LVD1-2.8F8C	N/A	N/A	N/A
		4.8 x 0.5	LVD1-4.8F5	LVD1-4.8F5C	N/A	N/A	N/A
		4.8 x 0.8	LVD1-4.8F8	LVD1-4.8F8C	N/A	N/A	N/A
		6.3 x 0.8	LVD1-6.3F	LVD1-6.3FC	ILVD1-6.3FC		ILND1-6.3FC
	1.5-2.5mm ² 16-14 AWG	2.8 x 0.5	N/A	LVD2-2.8F5C	N/A	N/A	N/A
		2.8 x 0.8	N/A	LVD2-2.8F8C	N/A	N/A	N/A
		4.8 x 0.5	LVD2-4.8F5	LVD2-4.8F5C	N/A	N/A	N/A
		4.8 x 0.8	LVD2-4.8F8	LVD2-4.8F8C	N/A	N/A	N/A
		6.3 x 0.8	LVD2-6.3F	LVD2-6.3FC	ILVD2-6.3FC		ILND2-6.3FC
	4.0-6.0mm ² 12-10 AWG	6.3 x 0.8	LVD5-6.3F	LVD5-6.3FC	ILVD5-6.3FC	N/A	ILND5-6.3FC

INSULATED MALE BULLET CONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED



unit: mm

	Wire Range	Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.96	VG1-4M	VG1-4MC	IVG1-4M	N/A	N/A
	1.5-2.5mm ² 16-14 AWG	3.96 4.95	VG2-4M VG2-5M	VG2-4MC VG2-5MC	IVG2-4M IVG2-5M	N/A	N/A
	4.0-6.0mm ² 12-10 AWG	4.95	VG5-5M	VG5-5MC	IVG5-5M	N/A	N/A

FULLY INSULATED FEMALE BULLET DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED



unit: mm

	Wire Range	To Fit Tab Size	Vinyl Flared Entry	Vinyl Flared W/ Copper Tube	Vinyl Molded	PC Molded	Nylon Molded
	0.5-1.5mm ² 22-16 AWG	3.96	LVG1-4F	LVG1-4FC	N/A	N/A	N/A
	1.5-2.5mm ² 16-14 AWG	3.96 4.95	LVG2-4F LVG2-5F	LVG2-4FC LVG2-5FC	N/A	N/A	N/A
	4.0-6.0mm ² 12-10 AWG	4.95	LVG5-5F	LVG5-5FC	N/A	N/A	N/A

FULLY NYLON INSULATED MALE & FEMALE BULLET DISCONNECTOR

MATERIAL: BRASS SURFACE: TIN PLATED




unit: mm

	Wire Range	Tab Size / To Fit Tab Size	Nylon Molded W/ Funnel Copper Tube
	0.5-1.5mm ² 22-16 AWG	3.95 3.95	LNG1-4FC LNG1-4MC
	1.5-2.5mm ² 16-14 AWG	4.55 4.55	LNG2-4FC LNG2-4MC

BUTT SPLICE

MATERIAL: BRASS SURFACE: TIN PLATED




unit: mm

	Wire Range	Vinyl Flared	Nylon Molded	Copper Insert
	0.5-1.5mm ² 22-16 AWG	VBS1 VBC1 VB1	INBS1 INBC1 INB1	Butted Seam Brass Butted Seam Copper Butted Seamless Copper Tube
	1.5-2.5mm ² 16-14 AWG	VBS2 VBC2 VB2	INBS2 INBC2 INB2	Butted Seam Brass Butted Seam Copper Butted Seamless Copper Tube
	4.0-6.0mm ² 12-10 AWG	VBS5 VBC5 VB5	INBS5 INBC5 INB5	Butted Seam Brass Butted Seam Copper Butted Seamless Copper Tube

HEAT SHRINK TERMINAL

MATERIAL: BRASS SURFACE: TIN PLATED


unit: mm

	Wire Range	Item Number	Copper Insert
	0.5-1.5mm ² 22-16 AWG	B1/ST	Seamless Copper Tube
	1.5-2.5mm ² 16-14 AWG	B2/ST	Seamless Copper Tube
	4.0-6.0mm ² 12-10 AWG	B5/ST	Seamless Copper Tube

QUICK SPLICE

MATERIAL: COPPER SURFACE: TIN PLATED

unit: mm

	Wire Range	Item Number	Material
	22-16 AWG	696100	P.P.
	16-14 AWG	696200	P.P.
	12-10 AWG	696500	P.P.

NOTE



MARROW LIN
DEVELOPMENT CO., LTD.

TAIPEI OFFICE

12F-2, No. 99, Sec. 2, Zhongshan N. Rd., Taipei, Taiwan

Tel : 886-2-2562-4521 Fax : 886-2-2561-0732

E-mail : service@marrowlin.com.tw

Website : www.marrowlin.com.tw